



Item Code: LBIO000X | Rev.: 2018-11-15 | Ver: 3.0

LIOS BIOIL Natural

Natural oil treatment for wooden floors





¤Description

LIOS BIOIL Natural is a natural oil treated for wooden floors. LIOS BIOIL Natural is very durable, protects the wood, giving a smooth effect enhancing the natural look of the wood grain.

*Characteristic	5
A 1: 1:	

Application	buffing machine, rubber trowel,
	floor polisher, sponge, cloths
Application temperature	+10°C ÷ +25°C
Thinning (if necessary)	LIOS SOLV
Surface dry time	12-24 h ⁽¹⁾
Total drying time	15 days ⁽¹⁾
Coverage	40-60 m²/L (depending on the
	porosity of the wood)
Storage stability	1 year ⁽²⁾
Packaging	1 L
Tool cleaning	DILUENTE DNE

- 1 at 20°C and 65% R.H.
- 2 in original sealed containers at temperatures between +10°C and +25°C

#How to use

LIOS BIOIL Natural has to be applied to wooden floors that have been filled, sanded with 120 paper grit, then use High Pro felt disc to make the surface absorbs the product evenly. Alternatively finish the floor with 150 paper grit.

Apply LIOS BIOIL Natural evenly and work the product in order to help its penetration into the wood. After 15-20 minutes buff the surface using a buffing machine with a white pad and a cloth to remove the excess of oil and having an uniform and smooth effect.

Use the rag for small environments.

In the case of very large porous fiber woods, repeat the entire cycle after 12-24 hours.

During the operation of felting of the second application it is advisable to use an absorbent cloth under the felt to facilitate the removal of excesses

After 24 hours, apply LIOS BALM Fissativo, OIL WOOD TRAFFIK, LIOS NATURAL Wax, LIOS HARD WAX BIOIL, LIOS HARD WAX BIOIL 3D, OIL WAX PLUS OIL WAX PLUS or LIOS HARD WAX BIOIL 90 (see technical data sheets).

Traffic on the surface after 24 hours, the product reaches maximum resistance after 15 days.

The maintenance of wooden floors treated with LIOS BIOIL Natural has to be done with LIOS range of products (see technical data sheets).

#Warnings

Cloths, rollers, pads used for the application (even sanding dust), must be soaked in water immediately after use in order to avoid the risk of self-ignition.

¤Label elements

- · Flammable liquid and vapour.· May be fatal if swallowed and enters airways.
- · Repeated exposure may cause skin dryness or cracking.· Contains . May produce an allergic reaction.
- · Keep away from heat / sparks / open flames / hot surfaces. No smoking. Keep container tightly closed. · Wear protective gloves / protective clothing / eye protection / face protection. · IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician. · IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower. In case of fire: use water to extinguish.

Contents:2-BUTANONO OXIME; FAT ACID, RAMIFIED C6-C19 COBALT SALTS; Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics;



¤Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_LIOS_BIOIL_Natural.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a pratical test by the user who assumes the full responsability of the final result of his work.