

Technical Datasheet

Chimiver

"Your floors partner"

Item Code: VFUP000X | Rev.: 2019-02-26 | Ver: 3.0

VELUREX Freshen Up

Water-based coating for intense maintenance of water-based lacquered wooden or resin floors



¤Description

VELUREX Freshen Up is a specially formulated water-based coating for intense maintenance of water-based lacquered wooden or resin floors. Its formula renews, protects and restores dull, scratched or signed wooden floors giving a matt effect. Specifically formulated without matting agents or waxes, gives a new look to each old and ruined flooring and allows for future coats of lacquer.

¤Characteristics

Application temperature	+10°C ÷ +25°C
Application	Base Mop Clean
Thinning (if necessary)	do not dilute
Coverage	1 L / 40-60 m²
Storage stability	1 year ⁽¹⁾
Packaging	1 L
Tool cleaning	water

in original sealed containers at temperatures between +10°C and +25°C

***Available Versions**

FRESHEN UP: gives a mat effect to the floor. FRESHEN UP SUPER OP: gives an extramat effect to the floor. FRESHEN UP SPORT: specific for sports flooring; in accordance to EN 14904 for slip resistance.

#How to use

Before using VELUREX FRESHEN UP clean the floor; use VELUREX Cleaner Star for cleaning lacquered wooden floors and VELUREX Resina Clean for cleaning resin floors.

The floor must be completely dry before apply VELUREX Freshen Up.

It is advisable to make a preliminary test before the application.

Prepare the white cloth microfiber of Base Mop Clean by slightly soaking with water.

Pour a wavy line of VELUREX Freshen Up on a defined section of the floor following the wood grain. Spread the product with a Base Mop Clean.

Notes

Do not use over any waxed or oiled floor.

Make sure the perfect adhesion of VELUREX Freshen Up onto UV water lacquer, if poor sand with 220 paper grit or green pad before the application.

Perform a small test if not sure of the results. The floor can be walked after 2-3 hours, but avoid heavy traffic and furniture replacement and rugs the first 12-24 hours.

The cleaning of the floor can be done after one week and has to be made with above mentioned VELUREX range of products.

Recommended use once or twice a month.

Warnings

Keep out of children's reach. Do not drink nor inhale. Avoid contact with eyes.

¤Label elements



¤Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_VELUREX_Freshen_Up.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a pratical test by the user who assumes the full responsability of the final result of his work.